



Model 90-125 M1 14" WOOD CUTTING BANDSAW

Optional accessories

- [Blades](#)
- [Riser attachment \(#90-130\)](#)
- [Excalibur universal bandsaw rip fence system \(#90-075A\)](#)

Cast-iron frame & precision-balanced aluminum wheels with replaceable rubber tires.

Closed stand model features a rigid one-piece welded stand.

Deluxe 2-position extruded aluminum rip fence, ideal for ripping thin stock and resawing taller work pieces.


Precision metal miter gauge with handle.


Deluxe blade guide bearings included.

2 cutting speeds for excellent results in either hard or soft woods.

Hinged door and easily accessible blade tensioning knob, for fast blade changes or adjustments.

Quick release blade tension lever.

 [View larger image](#)

 [Owner's manual](#)


 [Printable Page](#)

3/8" BLADE INCLUDED



**Deluxe 2-position
extruded aluminium rip
fence**

Wheel size	13 7/8" (353 mm)
Wheel speeds (2)	495 & 825 RPM
Maximum blade width	3/4" (19 mm)
Minimum blade width	1/8" (3.2 mm)
Blade length	93 1/2" (2375 mm)
Blade speeds (2)	1800 & 3000 LIN.FPM (549 & 915 LIN.MPM)
Table size	16" x 16" (406 x 406 mm)
Table tilt	0° TO 45° (RIGHT) / 0° TO 10° (LEFT)
Table height	42 3/4" (1085 mm)
Maximum width of cut	13 1/2" (343 mm)
Maximum depth of cut	6" (150 mm) (UP TO 12" WITH OPTIONAL RISER KIT)
Dust collection port	2 1/2" (63 mm)
Base dimensions (l x w)	18 5/8" x 15 3/4" (460 x 400 mm)
Motor (pre-wired 120 V)	1 HP, 120/240 V, 1 Ph, 10/5 A
Weight	224 LBS (102 kg)



**Quick-connect motor-to-
switch for easy set-up**



Blower device