



Model 90-880

HORIZONTAL RESAW BANDSAW

Dynamically balanced 23" cast-iron wheels.

Powerful drive motor for more efficient resawing.

Large 8" x 8" cutting capacity.

Equipped with an accurate, convenient digital read out, thickness controller.


Convenient roller type return conveyor for repetitive cutting.

Tilting, feed conveyor for repetitive bevel cuts.

Designed with faster, more profitable production in mind.

An oil mist cooling system provides high efficiency cooling on the blade.

Pneumatic pressure roller can be easily adjusted to stock thickness.

 [View larger image](#)

 [Printable Page](#)

CONTROL WITH DIGITAL DISPLAY

Maximum cutting capacity	8" x 8" (200 x 200 mm)
Distance from blade to conveyor	1/8" (3 mm) - 5 3/4" (145 mm)
Wheel size	23" x 1 1/4" (584 x 32 mm)
Blade length	173 1/4" (4400 mm)
Blade width	1 1/2" (38 mm)
Blade speed	4400 FPM (1320 MPM)
Conveyor belt size (w x l)	6 3/4" x 167 1/2" (172 x 4255 mm)
Feed speed (variable)	1.25 - 20 MPM
Conveyor tilt	0° TO 30° (FRONT DOWNWARD)
Conveyor height from floor	37 3/4" (985 mm)
Main motor M1	7 1/2 HP, 220 V, 1 Ph, 34.5 A
Main motor M2	10 HP, 220/440 V, 3 Ph
Main motor M3	10 HP, 600 V, 3 Ph
Blade lift motor	1/2 HP, 110/220 V, 7.3/3.7A, 1 Ph
Feed motor	1 HP, 220/440V, 3.4/1.7A, 3 Ph
Dust outlets	2 x 4" (102 mm)
Overall dimensions (l x w x h)	83 1/2" x 82 5/8" x 61" (2160 x 2100 x 1550 mm)
Weight	2068 LBS (938 kg)
