






Floor model



Line interrupter switch

 [View larger image](#)

 [Owner's manual](#)

 [Printable Page](#)

Model 75-160 M1 16" DRILL PRESS

Rotating, 45° tilting, crank-operated worktable with quick release clamp.

Forced opening switch need a re-start in case of power failure.

Adjustable spindle tension return spring.

Built-in lamp illuminates the drilling area. (Bulb not included)

Spindle is supported by high quality ball bearings.

Cast-iron pulleys reduce vibration.

Industrial 1/2 HP motor.

Heavy-duty positive depth stop for quick adjustment.

5/8" chuck with key.

| | |
|---------------------------|-----------------------------------|
| Swing | 16" (406 mm) |
| Drilling capacity | 5/8" (16 mm) |
| Chuck size | 5/8" (16 mm) |
| Spindle travel | 3 1/8" (80 mm) |
| Spindle distance to table | 30 5/16" (770 mm) |
| Spindle distance to base | 47 11/16" (1212 mm) |
| Table size | 10 1/2" (268 mm) |
| Column diameter | 2 7/8" (73 mm) |
| Number of speeds | 12 |
| Spindle speeds | 280-3000 RPM |
| Spindle taper | MT 2 |
| Overall height | 62" (1575 mm) |
| Base size | 10 7/8" x 19 3/16" (277 x 488 mm) |
| Motor | 1/2 HP, 110 V, 8 A |
| Weight | 134 LBS (61 kg) |

Optional accessories

-
- [Drill chuck with key \(#75-105\)](#)
 - [Keyless drill chuck \(#75-110\)](#)
 - [9" auger drill bit set \(#70-105\)](#)
 - [22 piece drill set 1/16" to 3/8" \(#70-020\)](#)
 - [Chuck guard \(#70-115A\)](#)
 - [Mortising attachment kit \(#70-905\)](#)
 - [9" vise-clamp \(#70-130\)](#)
 - [Drill press tool tray \(#70-125\)](#)
 - [16 piece forstner bit set \(#70-016\)](#)
 - [Self-centering pen drilling vise \(#70-120\)](#)
 - [12" x 24" universal drill table \(#70-135\)](#)
 - [17" x 32" universal drill table \(#70-140\)](#)
 - [25 piece - rubber drum sanding set \(#70-025\)](#)
 - [Abrasive sleeves 10 piece for item 70-025 \(#70-030\)](#)
 - [Laser pointer \(#70-300\)](#)
 - [Chuck guard \(#70-155\)](#)
 - [Drill press vise \(#95-140/150/160\)](#)
 - [Cross vises \(#95-400/500/600\)](#)
-