



Model 75-420 M1

BORING MACHINE

27 pcs 10 mm quick change spindle chucks included.

Fence and stop are fast set to the desired size.

Quick-release chucks for convenient boring bit changing.

Mechanical digital readout for accurate and consistent depth setting.

The motor is activated only during boring which minimizes power consumption & noise.

80" adjustable backfence with 2 stops.

Adjustable depth stop.

Easy change scale device.

Patent pending safety guard device to ensure operating safety.

 [View larger image](#)

 [Printable Page](#)

MANUAL OPERATION

Number of spindle drill heads	27 (LEFT 13 + RIGHT 14)
Spindle centers	1 1/4" (32 mm)
Quick change collet size	ø 3/8" (10 mm)
Spindle speed	3400 RPM
Table size (l x w)	43 5/16" x 15 3/4" (1100 x 400 mm)
Table height from floor	33 3/8" (847 mm)
Maximum depth of stroke	2 3/8" (60 mm)
Maximum drilling depth (boring bit to longitudinal fence)	12" (305 mm)
Longitudinal fence	80" (2032 mm)
Longitudinal fence stops	2 PCS
Cross fence stops	2 PCS
Motor	2 HP, 220 V, 1 Ph, 11.5 A
Weight	642 LBS (292 kg)
