
 [View larger image](#)

 [Printable Page](#)

Model 75-600 M1 RADIAL ARM DRILL PRESS

Extended head capacity allows for adjustable distance up to 20 1/2" from column to chuck.

Head tilts up to 30° left or right and swivels 360° for operations either on or off the table.

Large front mounted paddle style stop switch with lock-out safety feature to prevent unwanted or unintentional start-up.

Easy to read head tilt angle indicator for precise head tilt adjustment.

Dual head tilt locks prevent angle deviation under heavy loads.

Large machined cast-iron table.

Enclosed base cabinet with 2 storage shelves.

Cast-iron pulleys for smooth operation and reduced vibration.

See-through chuck guard included.

Optional accessories

- [9° auger drill bit set \(#70-105\)](#)
- [22 piece drill set 1/16" to 3/8" \(#70-020\)](#)
- [Mortising attachment kit \(#70-905\)](#)
- [9° vise-clamp \(#70-130\)](#)
- [Drill press tool tray \(#70-125\)](#)
- [16 piece forstner bit set \(#70-016\)](#)
- [Self-centering pen drilling vise \(#70-120\)](#)
- [25 piece - rubber drum sanding set \(#70-025\)](#)
- [Abrasive sleeves 10 piece for item 70-025 \(#70-030\)](#)
- [Drill press vise \(#95-140/150/160\)](#)
- [Cross vises \(#95-400/500/600\)](#)

Drilling capacity	5/8" (16 mm)
Chuck size	5/8" (16 mm)
Spindle taper	MT2
Swing	11 7/16" TO 43 5/16" (290 TO 1100 mm)
Spindle speeds (9)	290, 405, 465, 655, 780, 990, 1795, 2660 & 3725 RPM
Spindle travel	3 3/8" (85 mm)
Quill	2" (52 mm)
Spindle to table maximum	22 7/16" (570 mm)
Spindle to table minimum	7 1/2" (190 mm)
Table size	18 7/8" x 21 1/4" (479 x 540 mm)
Cabinet dimensions	19 6/8" x 29 1/8" x 31 1/2" (500 x 740 x 800 mm)
Column	3 5/32" (80 mm)
Head tilt	30° (RIGHT / LEFT)
Motor (prewired 110 V)	3/4 HP, 110/220 V, 12/6 A
Height	73 1/2" (1860 mm)
Weight	506 LBS (230 kg)
