



Model 75-700 M1

17" ELECTRONIC VARIABLE SPEED DRILL PRESS

Front mounted digital spindle speed display.

Electronic inverter variable control adjusts spindle speed from 280-3200 RPM.

Large precision ground cast-iron table with t-slots and coolant trough.

Front mounted positive control depth stop.

Solid head construction for accuracy and rigidity.

Slower speed options ideal for metal drilling applications.

Rack and pinion table height adjustment.

5/8" regular chuck with key included.


Included accessories:


- Chuck guard (#75-115C)
- Laser pointer (#75-300)


Swing	16 15/16" (430 mm)
Drilling capacity	3/4" (19 mm)
Chuck size	5/8" (16 mm)
Spindle travel	5 7/8" (150 mm)
Spindle distance to table	29" (737 mm)
Spindle distance to base	48 3/8" (1230 mm)
Table size	14 1/2" x 11 13/16" (370 x 300 mm)
Column diameter	3 1/8" (80 mm)
Spindle speeds	280 TO 1140 RPM & 800 TO 3200 RPM
Spindle taper	MT3
Base size	23 5/8" x 14" (600 x 355 mm)
Motor	1 HP, 220 V, 3 PH
Input power	110 V SINGLE PHASE ONLY
Weight	275 LBS (125 kg)

Optional accessories

- [9" auger drill bit set \(#70-105\)](#)
- [22 piece drill set 1/16" to 3/8" \(#70-020\)](#)
- [Mortising attachment kit \(#70-905\)](#)
- [9" vise-clamp \(#70-130\)](#)
- [Drill press tool tray \(#70-125\)](#)
- [16 piece forstner bit set \(#70-016\)](#)
- [Self-centering pen drilling vise \(#70-120\)](#)
- [12" x 24" universal drill table \(#70-135\)](#)
- [17" x 32" universal drill table \(#70-140\)](#)
- [25 piece - rubber drum sanding set \(#70-025\)](#)
- [Abrasive sleeves 10 piece for item 70-025 \(#70-030\)](#)
- [Chuck guard \(#70-175\)](#)
- [Drill press vise \(#95-140/150/160\)](#)
- [Cross vises \(#95-400/500/600\)](#)

 [View larger image](#)

 [Owner's manual](#)

 [Printable Page](#)

**DIGITAL INVERTER
ELECTRONIC VARIABLE
SPEED**