





Model 25-114QC M1


VARIABLE SPEED “MAXI-LATHE VF”



FORWARD / REVERSE SPINDLE ROTATION

 [View larger image](#)

 [Owner's manual](#)

 [Printable Page](#)

Forward or reverse spindle rotation selector switch for precision workpiece sanding and polishing.

Quick lock control levers easily position tool-rest.

Stable cast-iron frame, head and tailstock to reduce chatter and vibration for smoother turning.

Maximum distance of 17” between centers.

Maximum distance of 40” between centers with optional bed extension (Item #25-116).

Quick release lever for quick belt positioning changes.

3 variable speed ranges; 250-800, 550-1700 & 1200-3600 RPM.

Digital spindle speed display.

Features positive indexing in 15° increments – total 24 indexing positions.

Heavy-duty 1” diameter tool rest post.

Optional accessories

- [Stand \(#25-195N\)](#)
- [Stand \(#25-196\)](#)
- [23" bed extension \(#25-116\)](#)
- [MT #2 rolling center \(#25-145\)](#)
- [MT #2 screw end center \(#25-150\)](#)
- [MT #2 spur center \(#25-155\)](#)
- [MT #2 lathe center \(#25-170\)](#)
- [3" face plate \(#25-175\)](#)
- [6" face plate \(#25-185\)](#)
- [4 pc wood turning chisel set \(#25-210\)](#)
- [5 pc wood turning mini-chisel set \(#25-250\)](#)
- [4" - 4 jaw scroll chuck 1" -8 \(#25-105\)](#)
- [Self-centering pen dilling vise \(#70-120\)](#)

Included accessories:

- Live center
- Spur center
- Knouckout bar
- Safety glasses

Spindle speed	250 - 3600 RPM
Swing over bed	14" (356 mm)
Swing over tool rest	10 3/4" (273 mm)
Distance between centers	17" (432 mm)
Spindle thread	1" - 8 TPI
Tailstock through hole	3/8" (10 mm)
Morse taper	MT #2 (HEADSTOCK & TAILSTOCK)
Self ejecting travel	2" (51 mm)
Tool rest	6" (152 mm)
Face plate	3" (76 mm)
Indexing positions	24 X 15°
Motor	3/4 HP, 110 V, 5 A, 1950 RPM
Weight	93 LBS (42.5 kg)