



[View larger image](#)

[Printable Page](#)

## Models 26020 / 26020-1 20" WOOD TURNING LATHES - 4 speed / variable speed

High quality ribbed cast-iron headstock, tailstock, and bed.

Precision-machined bed guideways allow the tailstock and tool rest to slide smoothly.

Hinged headstock cover features a convenient speed ratio table.

Tailstock is equipped with an eccentric quick locking lever system.

High quality steel base including a one-piece cabinet with shelving.

Powerful North American designed, totally enclosed, fan cooled industrial motor.

All models equipped with a push-button "on/off" switch and a magnetic safety switch.

### Optional accessories

- [Spur center \(#1632SA\)](#)
- [Key chuck \(#34-25\)](#)
- [Screw center \(#1648\)](#)
- [Live center \(#2651MT1 / #2651MT2\)](#)
- [Cup center \(#1633SA\)](#)
- [60° dead center \(#1636\)](#)
- [4" tool rest \(#165\)](#)
- [12" tool rest \(#166\)](#)
- [24" tool rest \(#1624\)](#)
- [Right-angle tool rest \(#1621\)](#)
- [Telescopic floor stand \(#2643\)](#)
- [Knockout bar \(#2644\)](#)
- [Tool rest carriage \(#264SA\)](#)
- [12" extension \(#260-B12\)](#)
- [24" extension \(#260-B24\)](#)
- [60" extension \(#260-B60\)](#)
- [3" face plate \(#2637 / #2637-1\)](#)
- [6" face plate \(#2638 / #2638-1\)](#)
- [12" face plate \(#2647 / #2647-1\)](#)
- [4" - 4 jaw chuck \(#1653-1\) / 5" - 4 jaw chuck \(#2652\)](#)
- [4" riser block kit \(#269-4V / #269-VV\)](#)
- [Screw-on cast-iron arbor - female \(#2649 / #2649-1\)](#)
- [Adapter - female 1 1/4"-8 \(#2661\)](#)
- [Adapter - female 1 1/8"-8 \(#2662\)](#)
- [8 1/2" sanding disc \(#2642\)](#)
- [Cast-iron tool rest base \(#2645\)](#)
- [4" cast-iron extension post \(#2611\)](#)
- [4" cast-iron tool rest base \(#2614\)](#)
- [Cast-iron outboard turning bracket \(#2610 / 2610-20\) / Extension post \(#2611\) / 12" face plate \(#2647-1\)](#)
- [Wood lathe guard \(#25-160\)](#)
- [Vega professional wood turning lathe duplicator \(#Vega-D-36 / D-48 / D-96 / D-120\)](#)
- [4 pc wood turning chisel set \(#25-210\)](#)
- [5 pc wood turning mini-chisel set \(#25-250\)](#)
- [Wood lathe duplicator \(#25-036\)](#)
- [4" - 4 jaw scroll chuck 1 1/4" - 8 \(#25-605\)](#)
- [Self-centering pen dilling vise \(#70-120\)](#)



#### Tension release lever

Change speeds by releasing belt tension with the spring-loaded lever and repositioning the drive belt. (4 speed model 26020-1 only).



#### Steel headstock spindle

Variable speed models with precisionmachined, steel headstock spindle on 2 large, permanently lubricated sealed bearings. Spindle-mounted, dynamically balanced, cast-iron,V pulley and indexing mechanism. (4 speed models 26020 is equipped with a 4-step V pulley.)



#### Variable speed

Increase or decrease speed without stopping using the front mounted control lever. (Variable speed model 260-1 only).

#### Included accessories:

- [Spur center \(#1632SA\)](#)
- [Live center \(#2651-1\)](#)
- [Knock out bar \(#2644\)](#)
- [4" tool rest \(#165\)](#)
- [12" tool rest \(#166\)](#)
- [3" diameter face plate \(#2637\)](#)
- [6" diameter face plate \(#2638\)](#)
- [Tool rest carriage \(#264SA\)](#)
- [Gap filter block for bed \(#2645\)](#)

Swing-over bed capacity	20" (508 mm)
Swing-over gap capacity	24 1/2" (622.3 mm)
Max. Distance between centers	38" (965.2 mm)
Max. Distance with 60" extension (optional)	98" (2489 mm)
Floor to spindle center	45" (1043 mm)
Nose-inboard (r.h. thread)	1 1/4" – 8 (31.7 mm)
Nose-outboard (l.h. thread)	1 1/8" – 8 (28.5 mm)
Spindle bore	5/8" (16 mm)
Headstock / tailstock taper	Morse no. 2
Tailstock spindle travel	2" (50.8 mm)
Turning speeds	4 - #26020 Variable - #26020-1
Spindle speeds (#260)	600, 1050, 1720, 2800 RPM
Spindle speeds (#260-1)	375 TO 3300 RPM
Motor M2	2 HP, 230 V, 1 Ph, 8.3 A
Motor M3	2 HP, 230 V, 3 Ph, 6 A
Motor M4	2 HP, 208 V, 3 Ph, 6 A
Motor M5	2 HP, 600 V, 3 Ph, 2.2 A
Weight	524 LBS (238 kg) - #260 564 LBS (256 kg) - #260-1