
 [View larger image](#)

 [Printable Page](#)



Tension release lever

Spring-loaded quick release belt tension lever allows for quick speed changes.



Electronic control

Both models are equipped with a 4-step pulley system and a reversible electronic variable control.

Model 26020VRD-M2

20" WOOD TURNING LATHE - 4 variable & reversible speeds with electronic control

High quality ribbed cast-iron headstock, tailstock, and bed.

Precision-machined bed guideways allow the tailstock and tool rest to slide smoothly.

Hinged headstock cover features a convenient speed ratio table.

Tailstock is equipped with an eccentric quick locking lever system.

Cast-iron tool-rest carriage slides easily on guideways and locks securely with the locking lever mechanism.

High quality steel base including a one-piece cabinet with shelving. Large hinged door for easy access to the motor mechanism for cleaning and maintenance.

Powerful North American designed, totally enclosed, fan cooled industrial motor.

Conveniently positioned controls include: push-button "on/off" switch, speed control and a reverse button.

Included accessories:

- [Spur center \(#1632SA\)](#)
- [Live center \(#2651-1\)](#)
- [Knock out bar \(#2644\)](#)
- [4" tool rest \(#165\)](#)
- [12" tool rest \(#166\)](#)
- [3" diameter face plate \(#2637\)](#)
- [6" diameter face plate \(#2638\)](#)
- [Tool rest carriage \(#2614\)](#)
- [Gap filler block for bed \(#2645\)](#)

Swing-over bed capacity	20" (508 mm)
Swing-over gap capacity	24 1/2" (622.3 mm)
Max. Distance between centers	38" (965.2 mm)
Max. Distance with 60" extension (optional)	98" (2489 mm)
Floor to spindle center	45" (1143 mm)
Nose-inboard (r.h. thread)	1 1/4" - 8 (31.7 mm)
Nose-outboard (l.h. thread)	1 1/8" - 8 (28.5 mm)
Spindle bore	5/8" (16 mm)
Headstock/tailstock taper	Morse no. 2
Tailstock spindle travel	2" (50.8 mm)
Turning speeds (variable & reversible)	0 TO 3000 RPM
Minimum operating speed	150 RPM
Overall dimensions	60"x 21 1/2"x 49" (1524 x 546 x 1245mm)
Motor	2 HP, 230 V, 1 Ph, 8.3 A
Weight	562 LBS (255 kg)

Optional accessories

- [Spur center \(#1632SA\)](#)
- [Key chuck \(#34-25\)](#)
- [Screw center \(#1648\)](#)
- [Live center \(#2651MT1 / #2651MT2\)](#)
- [Cup center \(#1633SA\)](#)
- [60° dead center \(#1636\)](#)
- [4" tool rest \(#165\)](#)
- [12" tool rest \(#166\)](#)
- [24" tool rest \(#1624\)](#)
- [Right-angle tool rest \(#1621\)](#)
- [Telescopic floor stand \(#2643\)](#)
- [Knockout bar \(#2644\)](#)
- [Tool rest carriage \(#264SA\)](#)
- [12" extension \(#260-B12\)](#)
- [24" extension \(#260-B24\)](#)
- [60" extension \(#260-B60\)](#)
- [3" face plate \(#2637 / #2637-1\)](#)
- [6" face plate \(#2638 / #2638-1\)](#)
- [12" face plate \(#2647 / #2647-1\)](#)
- [4" - 4 jaw chuck \(#1653-1\) / 5" - 4 jaw chuck \(#2652\)](#)
- [4" riser block kit \(#269-4V / #269-VV\)](#)
- [Screw-on cast-iron arbor - female \(#2649 / #2649-1\)](#)
- [Adapter - female 1 1/4"-8 \(#2661\)](#)
- [Adapter - female 1 1/8"-8 \(#2662\)](#)
- [8 1/2" sanding disc \(#2642\)](#)
- [Cast-iron tool rest base \(#2645\)](#)
- [4" cast-iron extension post \(#2611\)](#)
- [4" cast-iron tool rest base \(#2614\)](#)
- [Cast-iron outboard turning lathe duplicator \(#Vega-D-367/D-48 / D-96 / D-120\)](#)
- [Wood lathe guard \(#25-160\)](#)
- [Vega professional wood turning lathe duplicator \(#Vega-D-367/D-48 / D-96 / D-120\)](#)
- [4 pc wood turning chisel set \(#25-210\)](#)
- [5 pc wood turning mini-chisel set \(#25-250\)](#)
- [Wood lathe duplicator \(#25-036\)](#)
- [4" - 4 jaw scroll chuck 1 1/4" - 8 \(#25-605\)](#)
- [Self-centering pen dilling vise \(#70-120\)](#)