

 [View larger image](#)

 [Owner's manual](#)

 [Printable Page](#)

### DOUBLE SIDED QUICK CHANGE KNIVES



Model 30-010 M1

## 13" SINGLE SURFACE PLANER

Powerful 2 HP 15 A motor with thermal overload protection.

Front and rear fold-down extension tables (12 L x 15 1/4 W) with end rollers for smooth easy stock feeding.

Top mounted rollers for multiple passes.

Convenient power cord storage brackets and inset lifting handles.

Dual position depth of cut adjustment handle mounts left or right – one full rotation equals 1/16".

Dual feed speeds for smooth planing with either soft or hard wood.

Adjustable pre-set depth gauge for accurate repeat cuts.

Easy to read graduated scale in both inches and metric.

Safety on/off switch with key. Unit cannot be started when key is removed from switch.

Snipe eliminating head lock.

Depth of cut indicator.

Knife changing magnets included.

---

Table area with extensions (l x w) 36 5/8" x 15 1/4" (930 x 387 mm)

Maximum planing width 13" (330 mm)

Maximum thickness of stock 6" (152 mm)

Minimum thickness of stock 1/8" (3 mm)

Minimum length of stock 5" (127 mm)

Maximum depth of cut (full width) 1/16" (1.5 mm)

Knives 2 - DOUBLE EDGED

Cutterhead speed 9500 RPM

Feed speeds (2) 18 & 26 FPM

Cuts per inch 88 / 61

Motor 2 HP, 120 V, 1 Ph, 15 A

Weight 77 LBS (35 Kg)

---

### Optional accessories

---

- [Stand \(#30-015\)](#)
  - [Replacement knives \(set of 2\) \(#30-013\)](#)
  - [Dust hood \(#30-020\)](#)
  - [Magnetic, micro-adjustable knife alignment gauge \(#30-025\)](#)
  - [A Dial - Gauge micro meter knife alignment \(#30-050\)](#)
  - [Cutter head-table alignment block \(set of 2\) \(#30-040\)](#)
-