



Built-in Wheels

Model 30-125CE M1 15" SINGLE SURFACE PLANER

Heavy-duty enclosed stand protects motor from dust and provides a stable work station.

Heavy-duty cast-iron frame reduces vibration for more precise planing.

Four-post design provides added stability to keep the table aligned with the cutter head.

5" offset dust chute for efficient dust collection.

Knife setting gauge included.

Triple V-belt drive for greater power.

Magnetic safety switch for added safety.

Two (2) convenient 15" top mounted return rollers allow smooth stock handling for consecutive planing.

Base is equipped with four (4) lockable wheels to allow easy movement around the workshop.

The head of the machine is equipped with anti-kickback fingers.


Two (2) lock-knobs secure the table for greater precision.

Large cast-iron extension wings.

Polyurethane out-feed rollers.

Optional accessories

- Hi-speed steel model replacement blade set - number of knives: 3 / length: 15" (#30-130)
- Magnetic, micro-adjustable knife alignment gauge (#30-025)
- A Dial - Gauge micro meter knife alignment (#30-050)
- Cutter head-table alignment block (set of 2) (#30-040)

 [View larger image](#)

 [Printable Page](#)

**LARGE CAST-IRON
EXTENSION WINGS**



OPTIONAL

ITEM #125H : 15" HELICAL CUTTER HEAD
4 rows, total: 42 inserts

Table area with extensions	15" x 49" (380 x 1245 mm)
Maximum planing width	14 7/8" (378 mm)
Maximum thickness of stock	6" (152 mm)
Minimum thickness of stock	3/8" (10 mm)
Minimum length of stock	6 1/2" (165 mm)
Maximum depth of cut	1/8" (3 mm)
Cutter head diameter	2 7/8" (73 mm)
Number of knives	3 (DOUBLE EDGE)
Cutter head speed	5000 RPM
Feed speeds (2)	16 & 20 FPM (4.87 & 6.1 MPM)
Cuts per inch	78.13 @ 16 FPM & 62.5 @ 20 FPM
Motor	3 HP, 220 V, 1 Ph, 15 A
Weight	536 LBS (256 kg)