



Model 15-245 M1

25" HORIZONTAL DOUBLE DRUM SANDER

Steel frame and heavy-duty base for greater stability. Includes dual access doors.

High quality conveyor belt for long service life.

Parallelism between the sanding drums and the conveyor table is adjusted by convenient eccentric adjustment lever.

Large hand wheel adjusts conveyor table height.

Two (2) magnetic safety switches for main motor and conveyor motor.

Graduated depth scale in both inches and metric to indicate sanding thickness.

Rear drum adjustment lever with convenient reference scale, no tools or gauge blocks required.


High quality hard-rubber coated drums for longer sandpaper life and less slippage.

Convenient front mounted adjustment knobs for tool-free tracking adjustments.

In-feed safety bar with emergency stop.

Amp meter for motor load indicator.

Dual port 4" efficient dust control system.

 [View larger image](#)

 [Printable Page](#)

VARIABLE SPEED CONVEYOR BELT



Rear drum adjustment lever

Maximum sanding width	25" (635 mm)
Maximum sanding thickness	5 5/16" (135 mm)
Minimum sanding thickness	1/4" (6.4 mm)
Minimum sanding length	8 7/16" (215 mm)
Table dimensions	25" x 25" (635 x 635 mm)
Drum diameter	6" (152 mm)
Drum speed	1540 RPM
Feeding speed (variable)	3.7 TO 14.2 FPM (1.2 TO 4.7 M/MIN)
Main motor	5 HP, 220 V, 1 Ph, 22.3 A
Conveyor motor	1/4 HP
Weight	805 LBS (365 kg)
