



Model 15-250 M1

24" HORIZONTAL DOUBLE DRUM SANDER - 3 HP

Optional accessory

-
- [Sanding belts](#)
-

Steel frame and heavy-duty base for greater stability.

High quality conveyor belt for long service life.

Parallelism between the sanding drums and the conveyor table is adjusted by convenient adjustment screws.

Large hand wheel adjusts conveyor table height.


Magnetic safety switch.


Two (2) 4" dust outlets.


Graduated depth scale in both inches and metric to indicate sanding thickness.

Conveyor belt motor equipped with a safety switch with removable key.

Dual v-belt driven sanding drums.

 [View larger image](#)

 [Owner's manual](#)

 [Printable Page](#)

VARIABLE SPEED CONVEYOR BELT



Two dynamically balanced 5" aluminum drums for extremely smooth operation

Maximum sanding width	24" (610 mm)
Maximum sanding thickness	5" (127 mm)
Minimum sanding thickness	1/4" (6 mm)
Minimum sanding length	5" (127 mm)
Drum diameter	5" (127 mm)
Drum speed	1550 RPM
Feeding speed	3 TO 20 FPM (0.93 to 6.2 M/MIN) (VARIABLE)
Base dimensions (l x w)	42 1/2" x 16 1/2" (1079.5 x 419 mm)
Main motor	3 HP, 220 V, 1 Ph, 15 A
Conveyor motor	1/6 HP
Weight	570 LBS (259 kg)
