

Model 50-200R M1

10" Left Tilt 2 HP Table Saw



Combination riving style splitter and see-through blade guard with anti-kickback pawls, and a second European style riving knife also included.

Large precision-ground 44" x 27" cast-iron table with two extension wings.

4" dust port allows easy connection to a dust collection system.

Large paddle-style stop switch.

Ruggedly built saw carriage with solid cast-iron cabinet mounted trunnions.

Large motor access door for quick cleaning and easier maintenance.

Convenient arbor lock for fast one tool blade changes.

Equipped with a sturdy, east to adjust, T-fence design rip fence system.


Powerful 2 HP motor with multi-groove V-belt drive for longer belt life and more efficient transfer of power.


Onboard storage mounts for wrench, rip fence and miter gauge.

Optional accessories

- [10" x 27" solid cast-iron extension wing with router insert rings \(#50-195\)](#)
- [Zero-clearance table saw insert \(#50-203\)](#)
- [Assorted 10" carbide blades](#)
- [DADO insert \(#50-202\)](#)

 [View larger image](#)

 [Owner's manual](#)

 [Printable Page](#)

Blade diameter	10" (254 mm)
Arbor diameter	5/8" (16 mm)
Arbor tilt range	0° TO 45° (TO LEFT)
Maximum depth of cut at 90°	3" (77 mm)
Maximum depth of cut at 45°	2 1/4" (54 mm)
Max. rip to left of blade:	8" (203 mm)
Max. rip to right of blade:	30" (762 mm)
Dado capacity	13/16" (21 mm)
Dust port diameter	4" (102 mm)
Arbor speed	4000 RPM
Table height	36" (914 mm)
Table size (w/extension wings)	44" x 27" (1118 x 686 mm)
Table size (w/o extension wings)	20" x 27" (508 x 686 mm)
Base dimensions	20" x 20" (508 x 508 mm)
Motor (pre-wired 230 V)	2 HP, 115/230 V, 19.5/9.5 A
Weight	321 LBS (146 kg)
