

Model 50-240GT M1

## 10" GRANITE TOP TABLE SAW - Left Tilt



Quick release combination riving style splitter and blade guard with anti-kickback pawls and a second European style riving knife also included.

Large, precision-ground and polished, 40" x 27" solid granite table with two extension wings, for unsurpassed stability; will never twist or warp and cannot rust or corrode.

4" dust port allows easy connection to a dust collection system.

Large paddle-style stop switch.

Ruggedly built saw carriage with solid cast-iron, cabinet mounted trunnions.

Large motor access door for quick cleaning and easier maintenance.

Equipped with a sturdy, easy to adjust, T-fence design rip fence system.

Dual capacitor 1 3/4 HP motor, for smooth start-up and quiet operation, with plenty of power for tough cutting applications.

### Optional accessories

---

- [Dado insert \(#50-241\)](#)
  - [Universal mobile base \(#50-025\)](#)
  - [Deluxe push stick & holder \(#T-Stick / #T- Bracket\)](#)
  - [Excalibur overarm blade cover system \(#50-EXBC\)](#)
  - [Osborne miter guide \(#50-EB3\)](#)
  - [Tenoning jig \(#50-050\)](#)
  - [7 piece - deluxe 8" Dado blade set \(#55-185\)](#)
  - [3 piece - 10" x 5/8" carbide blade assortment with deluxe carrying case \(#55-300\)](#)
  - [10" & 12" carbide tipped saw blades](#)
  - [27" x 36" melamine extension table \(#50-105\) / Steel adjustable support leg set \(2\) \(#50-115\)](#)
  - [Deluxe cast-iron miter gauge \(#50-145\)](#)
- 



[View larger image](#)



[Owner's manual](#)



[Printable Page](#)

---

Blade diameter	10" (254 mm)
Arbor diameter	5/8" (16 mm)
Arbor tilt range	0° TO 45° (to left)
Maximum depth of cut at 90°	3 3/16" (82 mm)
Maximum depth of cut at 45°	2 5/16" (60 mm)
Dado capacity	3/4" (19 mm)
Dust port diameter	4" (102 mm)
Arbor speed	4250 RPM
Table height	35 3/4" (910 mm)
Table size (w/extension wings)	40" x 27" (1016 x 686 mm)
Table size (w/o extension wings)	20" x 27" (508 x 686 mm)
Base dimensions (l x w)	19 1/2"x 22" (495 x 560 mm)
Motor (pre-wired 120 V)	1 3/4 HP, 120/240 V, 15/7.5 A
Weight	476 LBS (216 kg)

---