



ITEM 40-850

## PNEUMATIC OVERARM ROUTER

**Note: Requires a portable router and bits and a compressed air source that are not included.**

Steel base, arm and stand for smooth stable operation.

Adjustable pneumatic up and down feed speed control.

Foot pedal activated pneumatic feed lowers the router into the workpiece leaving hands free to control the workpiece.


Removable fence with graduated scale for both fence or pin routing applications.

Six (6) adjustable depth settings.

Wide, phenolic coated table for long life and friction free performance.

Includes 4 router adapters to accommodate most brand name

1 1/2 HP to 3 1/2 HP portable routers.

 [View larger image](#)

 [Printable Page](#)

---

Table size (w x d x thick)	23 1/2" x 30" x 1/2" (597 x 762 x 19 mm)
Table height	32" (825 mm)
Overall dimensions (w x d x h)	36 1/4" x 36" x 60 1/2" (920 x 914 x 1537 mm)
Throat capacity	18" (457 mm)
Maximum head stroke	4 1/2" (115 mm)
Maximum distance spindle to table	9" (229 mm)
Maximum distance housing to table	11" (280 mm)
Maximum distance center to fence	12" (304 mm)
Pre-set stops	20, 40, 60, 80, 100 mm
Router adapter sizes	3 1/4", 3 21/64", 3 1/2" & 4 13/64" (82, 85, 89 & 106 mm)
Router housing	4 1/2" (114 mm) dia.
Table pins (3)	3/16" x 1/4", 5/16" x 3/8", 7/16" x 1/2" (4.8 x 6.4, 8 x 9.5, 11 x 13 mm)
Required operating air pressure	80 PSI
Maximum air pressure	100 PSI
Compatible routers	1 1/2 HP ~ 3 1/2 HP
Weight	170.5 LBS (77.5 kg)

---