





Available on special order

 [View larger image](#)

 [Printable Page](#)

Model SS-032

1 1/4" INDUSTRIAL SPINDLE SHAPER - Interchangeable Spindle

Enclosed, one-piece, high-quality steel cabinet for greater strength and stability.

Large ribbed cast-iron table with miter gauge T-slot.

Independently adjustable, cast guide fence system.

Hold-down guide system comprised of 4 guide rollers on steel supports & cast blocks with locking levers.

Aluminum spindle cover for greater safety particularly when operating without the fence.

Interchangeable 1 1/4" precisionmachined, high-quality steel spindle, fitted with a "Morse No. 4 taper" (MT4), with spacers, washer & nut for various types of knives.

Large accessible cast hand wheel with handle for easy spindle adjustment.

Optional accessories

- [Heavy-duty cast-iron miter gauge \(#1950\)](#)
- [Hub cutter set \(#3070\)](#)
- High-quality, interchangeable steel spindle with spacers, washer and steel nut. Capacity: 3/4" (19 mm) (#3208SA)
- High-quality, interchangeable steel spindle with spacers, washer and steel nut. Capacity: 1" (25.4 mm) (#3212SA)
- [3" fiberglass dust collection outlet \(#3078\)](#)



Electric control box

Dual magnetic controls, one for "forward" and one for "reverse", in an overload protected control box, with one stop button for both.



Spindle and disc brake

Heavy-duty cast-iron bearing housing with machined guideways & adjustment gib. Quality steel spindle, on heavy-duty sealed bearings. Disc brake fitted to the spindle for quick stops and tool changes.

Table size	36" x 30" (915 x 762 mm)
Table height	33 1/2" (851 mm)
Guide fence dimensions	16 1/2" x 4 1/2" (420 x 114 mm)
Overall fence dimensions	42" x 4 1/2" (1067 x 114 mm)
Distance in front of spindle	16 1/2" (420 mm)
Spindle diameter	1 1/4" (32 mm)
Spindle speed (4 - reversible)	3600, 5000, 7200 & 9000 RPM
Vertical spindle travel	6" (127 mm)
Maximum diameter of tool	8" (203 mm)
Maximum height of tool	5" (127 mm)
Outside table insert diameter	5 1/2" & 8 3/4" (140 & 222 mm)
Table openings	3 1/2", 5 1/2" & 8 3/4" (89, 140 & 222 mm)
Motor M2	3 HP, 230 V, 1 Ph, 13.7 A
Motor M3	5 HP, 230 V, 3 Ph, 12 A
Motor M4	5 HP, 208 V, 3 Ph, 12 A
Motor M5	5 HP, 600 V, 3 Ph, 4.8 A
Weight	800 LBS (363 kg)