

Items 95-400, 95-500 & 95-600

## CROSS VISES



Rugged cast-iron construction for a lifetime of durability.

Dual crank-type handles control movement of jaws in each direction.


Fast action, "Acme" type threaded rod, guides the jaws and maintains accurate alignment.


Removable jaws can be replaced with optional prismatic jaws for gripping tubular, irregularly shaped or round work pieces.

Multi-directional movement without removing the vise from the drill.

## Optional accessories

- [Prismatic jaws \(#95-450 / 95-550 / 95-650\)](#)

 [View larger image](#)

 [Printable Page](#)

---

### 95-400

Jaw width	4" (102 mm)
Jaw depth	1 3/8" (35 mm)
Jaw opening	3 13/32" (86.4 mm)
Overall depth	5 3/8" (136.5 mm)
Longitudinal travel	5 13/16" (147.6 mm)
Cross travel	4" (102 mm)
Weight	20.9 LBS (9.5 kg)

---

### 95-500

Jaw width	5" (127 mm)
Jaw depth	1 9/16" (39.7 mm)
Jaw opening	4 3/4" (120.6 mm)
Overall depth	5 29/32" (150 mm)
Longitudinal travel	7" (178 mm)
Cross travel	5" (127 mm)
Weight	33 LBS (15 kg)

---

### 95-600

Jaw width	6" (152 mm)
Jaw depth	1 5/8" (41 mm)
Jaw opening	5 3/4" (146 mm)
Overall depth	6 1/2" (165 mm)
Longitudinal travel	8" (203.2 mm)
Cross travel	6" (152 mm)
Weight	44.4 LBS (20.2 kg)

---