



Model 25-365 M1

11" X 28" VARIABLE SPEED METAL LATHE - with stand

Variable speed, which is easy to change.

Digital speed display.

Removable tool post for quick tool change.


Steady and follow rest included.


Apron handwheel with safety design.

Pulley case and chuck guard both equipped with auto shut-off safety switch.

Low voltage transformer.

Full length lead screw cover / guard for operator safety.

 [View larger image](#)

 [Printable Page](#)

Included accessories:

- Face plate
- Four jaw chuck

Swing over bed	11" (280 mm)
Swing over cross slide	7" (170 mm)
Distance between centers	28" (711 mm)
Bed width	7" (180 mm)
Spindle bore	1" (26 mm)
Taper in spindle nose	MT4
Spindle speeds (variable)	50-2150 RPM
Tailstock taper	MT2
Tailstock travel	3" (80 mm)
Number/range of metric threads	8 / 0.5 - 3 mm
Number/range of imperial threads	18 / 8-56 TPI
Longitudinal range	0.0025" - 0.015"
Maximum compound slide travel	2 2/5" (60 mm)
Maximum cross slide travel	5" (130 mm)
Maximum carriage travel	19" (495 mm)
Overall Dimensions (l x w x h)	52" x 28" x 50" (1310 x 700 x 1270 mm)
Motor	2 HP, 220V, 1Ph, 9A
Weight	605 LBS (275 kg)
