





Shown with optional stand
(#75-855)

 [View larger image](#)

 [Printable Page](#)

Model 75-850 M1 MILLING / DRILLING MACHINE

Will allow you to do drilling, milling, tapping, boring and reaming.

Head swivels 360°.

Zero setting dials.

12 speeds from 120 to 2500 RPM.

Adjustable gibs on table.

Adjustable stops on table.

Heavy-duty tapered roller bearing spindle.

Standard accessories: 1/2" chuck, 1/2" chuck arbor, 3" cutter, 3" cutter arbor, angle vise.

Optional accessories

- [Stand \(#75-855\)](#)
 - [Table feeder - 110V \(#75-860\)](#)
 - [Table feeder - 110/220V \(#75-865\)](#)
 - [9" vise-clamp \(#70-130\)](#)
 - [17" x 32" universal drill table \(#70-140\)](#)
 - [52 piece 1/2" clamping kit \(#70-520\)](#)
 - [Drill press vise \(#95-140/150/160\)](#)
 - [Cross vises \(#95-400/500/600\)](#)
-

Included accessories:

- [1/2" chuck](#)
 - [1/2" chuck arbor](#)
 - [3" cutter arbor](#)
 - [3" cutter](#)
 - [Angle vise](#)
-

Drilling capacity	1 1/4" (32 mm)
Face mill capacity	3" (76 mm)
End mill capacity	3/4" (19 mm)
Swing	15 7/8" (405 mm)
Max. distance spindle nose to table	18" (480 mm)
Spindle taper	R-8
Spindle stroke	5" (130 mm)
Diameter of spindle sleeve	3" (75 mm)
Spindle speeds (12)	120-2500 RPM
Forward and backward table travel	6 1/2" (165 mm)
Right and left table travel	14 1/8" (360 mm)
Work area table	28 3/4" x 8 1/4" (730 x 210 mm)
Motor	2 HP, 220 V, 1 Ph, 9 A
Weight	660 LBS (300 kg)
