



 [View larger image](#)

 [Printable Page](#)

Model 75-915 M1

ELECTRONIC VARIABLE SPEED DRILL PRESS

Powerful 2 HP motor provides plenty of power to suit a wide variety of drilling applications.

Front mounted digital spindle speed display.

Electronic variable speed control adjusts spindle speed from 150 to 3000 RPM.

Large, precision-ground table with T-slot for easy set-ups.

Large mushroom style emergency stop button for quick easy shut-off.

Front mounted positive control depth stop.

Solid head construction for accuracy and rigidity.

Front or side rack and pinion gear assembly table height adjustment.

Timing belt driven transmission to avoid slippage.

Forward/reverse tapping system.

Optional accessories

- [Coolant system \(#75-920\)](#)
 - [Arbor \(#75-133\)](#)
 - [9" vise-clamp \(#70-130\)](#)
 - [12" x 24" universal drill table \(#70-135\)](#)
 - [17" x 32" universal drill table \(#70-140\)](#)
 - [Drill chuck with key \(#75-105\)](#)
 - [Keyless drill chuck \(#75-110\)](#)
 - [Chuck guard \(#70-115\)](#)
 - [52 piece 1/2" clamping kit \(#70-520\)](#)
 - [Drill press vise \(#95-140/150/160\)](#)
 - [Cross vises \(#95-400/500/600\)](#)
-

Drilling Capacity	Steel: 1 3/16" (30 mm) / Cast Iron: 1 1/4" (32 mm)
Tapping Capacity	Steel : 5/8" (16 mm) / Cast Iron: 3/4" (19 mm)
Swing	16" (408 mm)
Spindle Taper	MT #3
Spindle Travel	5 9/32" (134 mm)
Quill Diameter	2 7/16" (62 mm)
Column Diameter	3 5/8" (92 mm)
Spindle Nose to Table	26 9/16" (675 mm)
Spindle Nose to Base	44 1/16" (1120 mm)
Table Size	18 1/8" x 14 5/32" (460 x 360 mm)
Table Slots	2 x 1/2" (14 mm)
Base Size	14 3/8" x 21" (365 x 535 mm)
Spindle Speed	150 - 3000 RPM
Motor	2 HP, 220V/3 PH/ 7AMP
Input Power	220 V, 1 Ph Only
Coolant Motor (Optional)	1/8 HP
Weight	403 LBS (183 kg)
