



Model 50-075 M1 10" TABLE SAW

Heavy-duty precision cast iron ribbed table with miter gauge "t" slot.
2 steel extension wings.

Heavy-duty open steel stand and frame for greater stability.

Large hand wheels quick and easy blade height and angle adjustment.

Angle bracket for switch mounts to front fence rail.

See-through blade guard with splitter and anti-kickback fingers.


30" deluxe precision rip fence for quick, precise adjustments.

Equipped with onboard storage mounts for wrenches, rip fence and miter gauge.

Powerful 110/220 Volt - dual capacitor - 2 HP motor.

Optional accessories

- [Zero-clearance table saw insert \(#50-085\)](#)
 - [Excalibur overarm blade cover system \(#50-EXBC\)](#)
 - [Osborne miter guide \(#50-EB3\)](#)
 - [Tenoning jig \(#50-050\)](#)
 - [Magic molder \(#50-START\)](#)
 - [7 piece - deluxe 8" Dado blade set \(#55-185\)](#)
 - [3 piece - 10" x 5/8" carbide blade assortment with deluxe carrying case \(#55-300\)](#)
 - [10" & 12" carbide tipped saw blades](#)
 - [Clamping miter gauge with t-slot bar \(#50-140\)](#)
-

 [View larger image](#)

 [Printable Page](#)

Blade diameter	10" (255 mm)
Arbor diameter	5/8" (16 mm)
Arbor tilt range (right tilt)	0° to 45°
Max. depth of cut at 90°	3" (77 mm)
Max. depth of cut at 45 °	2 1/8" (54 mm)
Max. rip to left of blade	12" (305 mm)
Max. rip to right of blade	30" (763 mm)
Arbor speed	4200 RPM
Table size	27" x 39 1/2" (686 x 1003 mm)
Base Dimensions	21" x 26" (533 x 660 mm)
Motor (pre-wired 110V)	2 HP, 110/220 V, 15/7.5 A
Weight	237 LBS (108 KG)
