



Model 50-225R M1 10" TILTING ARBOR SAW

New! Excalibur aluminum T-fence

Large, precision-ground, 44" x 27" cast-iron table with two extension wings.

4" dust port allows easy connection to a dust collection system.

Safety key switch.


Ruggedly built saw carriage with solid cast-iron trunnions.


Large motor access door for quick cleaning and easier maintenance.


Convenient arbor lock for fast one-tool blade changes.

Optional accessories


- [Zero-clearance table saw insert \(#50-020R\)](#)
- [DADO insert \(#50-230R\)](#)
- [Heavy-duty mobile base \(#50-030\)](#)
- [Excalibur sliding table \(50-SLT40P\)](#)
- [Excalibur sliding table \(50-SLT60P\)](#)
- [Excalibur overarm blade cover system \(#50-EXBC\)](#)
- [Osborne miter guide \(#50-EB3\)](#)
- [Tenoning jig \(#50-050\)](#)
- [7 piece - deluxe 8" Dado blade set \(#55-185\)](#)
- [3 piece - 10" x 5/8" carbide blade assortment with deluxe carrying case \(#55-300\)](#)
- [10" & 12" carbide tipped saw blades](#)
- [Deluxe cast-iron miter gauge \(#50-145\)](#)

 [View larger image](#)

 [Owner's manual](#)

 [Printable Page](#)

[Click here to open a pdf copy of our document "What is a riving knife?"](#)



New!

Combination riving style splitter and blade guard with anti-kickback pawls and a second European style riving knife also included.

Blade diameter	10" (254 mm)
Arbor diameter	5/8" (16 mm)
Arbortilt range	0° À 45°
Max. depth of cut at 90°	3 1/8" (80 mm)
Max. detph of cut at 45 °	2 1/4" (57 mm)
Dado capacity	3/4" (19 mm)
Dust port diameter	4" (102 mm)
Arbor speed	4200 RPM
Table height	35 3/8" (899 mm)
Table size (w/extension)	44" x 27" (1118 x 686 mm)
Table size (w/o extension)	20" x 27" (508 x 686 mm)
Base dimensions (L x W)	20" x 20" (508 x 508 mm)
Motor (Pre-wired for 110 V)	2 HP, 110/220 V, 13/6.5 A
Weight	312 LBS (142 kg)